

Package: delarr (via r-universe)

May 15, 2026

Type Package

Title Lazy Delayed Arrays with Fused Execution

Version 0.0.0.9000

Description Provides a lightweight delayed array abstraction with tidy-friendly verbs, expression fusion, and pluggable storage backends.

URL <https://bbuchsbaum.github.io/delarr/>,
<https://github.com/bbuchsbaum/delarr>

BugReports <https://github.com/bbuchsbaum/delarr/issues>

License MIT + file LICENSE

Depends R (>= 4.1)

Imports rlang, hdf5r, mmap

Suggests matrixStats, shard, testthat (>= 3.1.0), knitr, rmarkdown

Remotes bbuchsbaum/shard

VignetteBuilder knitr

Encoding UTF-8

LazyData false

Config/testthat/edition 3

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Config/pak/sysreqs libhdf5-dev

Repository <https://bbuchsbaum.r-universe.dev>

Date/Publication 2026-04-15 12:18:15 UTC

RemoteUrl <https://github.com/bbuchsbaum/delarr>

RemoteRef HEAD

RemoteSha cdad570a331a67a4483b27197f7ca05a33042b77

Contents

[.delarr	3
as.matrix.delarr	3
block_apply	4
collect	5
collect_shard	6
colMeans2	7
colMeans2.delarr	8
d_aperm	8
d_center	9
d_detrnd	9
d_map	10
d_map2	11
d_matmul	12
d_reduce	12
d_reduce_many	13
d_scale	14
d_transpose	15
d_where	15
d_zscore	16
delarr	17
delarr_backend	17
delarr_hdf5	19
delarr_mem	20
delarr_mmap	20
delarr_seed	21
delarr_seed_nd	22
delarr_shard	23
dim.delarr	24
dim.delarr_seed	25
dimnames.delarr	25
explain	26
hdf5_writer	26
Ops.delarr	27
optimize_delarr	28
print.delarr	28
profile_collect	29
read_hdf5	29
rowMeans2	30
rowMeans2.delarr	31
shard_writer	31
write_hdf5	32

[.delarr	<i>Subset a delayed array</i>
----------	-------------------------------

Description

Performs array-style slicing lazily, capturing the indices in the DAG. For 2D arrays, standard `x[i, j]` syntax works. For N-d arrays, provide one index expression per dimension: `x[i, j, k, ...]`.

Usage

```
## S3 method for class 'delarr'
x[..., drop = FALSE]
```

Arguments

<code>x</code>	A delarr.
<code>...</code>	Index expressions, one per dimension. Missing indices select all.
<code>drop</code>	Logical indicating whether to drop dimensions (ignored lazily).

Value

A delarr containing the slice operation.

<code>as.matrix.delarr</code>	<i>Materialise a delayed matrix as a base matrix</i>
-------------------------------	--

Description

Materialise a delayed matrix as a base matrix

Usage

```
## S3 method for class 'delarr'
as.matrix(x, ...)
```

Arguments

<code>x</code>	A delarr.
<code>...</code>	Passed to <code>collect()</code> .

Value

A base matrix containing the realised data.

`block_apply`*Apply a function to streamed matrix blocks*

Description

Evaluates a delarr slice-by-slice, materialising manageable chunks for further processing without realising the full matrix.

Usage

```
block_apply(  
  x,  
  margin = c("cols", "rows"),  
  size = 16384L,  
  fn,  
  parallel = FALSE,  
  workers = NULL  
)
```

Arguments

<code>x</code>	A delarr object.
<code>margin</code>	Dimension along which to chunk ("cols" or "rows").
<code>size</code>	Approximate chunk size.
<code>fn</code>	Function applied to each materialised chunk.
<code>parallel</code>	Logical; process chunks in parallel when possible.
<code>workers</code>	Number of worker processes for parallel execution.

Value

A list of results returned by `fn`.

Examples

```
mat <- matrix(1:20, nrow = 4, ncol = 5)  
darr <- delarr(mat)  
  
# Apply function to column chunks  
col_maxes <- block_apply(darr, margin = "cols", size = 2L, fn = function(block) {  
  apply(block, 2, max)  
})  
unlist(col_maxes)  
  
# Apply function to row chunks  
row_means <- block_apply(darr, margin = "rows", size = 2L, fn = function(block) {  
  rowMeans(block)  
})
```

```
unlist(row_means)
```

 collect

Materialise a delayed matrix

Description

Streams column chunks from the backing seed, applying deferred operations and optional reductions on the fly. By default the result is returned as a base matrix or vector; alternatively, supply a writer via `into` to stream the output elsewhere (e.g., `hdf5_writer()`).

Usage

```
collect(
  x,
  into = NULL,
  chunk_size = NULL,
  chunk_margin = c("cols", "rows"),
  target_bytes = NULL,
  parallel = FALSE,
  workers = NULL,
  optimize = TRUE
)
```

Arguments

<code>x</code>	A <code>delarr</code> object.
<code>into</code>	Optional writer or callback used to receive streamed chunks.
<code>chunk_size</code>	Optional chunk size along <code>chunk_margin</code> .
<code>chunk_margin</code>	Chunking axis for non-reduction collection.
<code>target_bytes</code>	Optional memory budget (bytes) used to adapt chunk size.
<code>parallel</code>	Logical; attempt parallel chunk execution when safe.
<code>workers</code>	Number of worker processes when <code>parallel = TRUE</code> .
<code>optimize</code>	Logical; run lightweight DAG optimizations before evaluation.

Value

A realised matrix/vector, or `NULL` invisibly when writing to `into`.

Examples

```
# Basic materialization
mat <- matrix(1:12, nrow = 3, ncol = 4)
darr <- delarr(mat)
collect(darr)

# Collect after lazy operations
result <- darr |>
  d_map(~ .x^2) |>
  collect()
result
```

 collect_shard

Parallel collect using shard's shared-memory workers

Description

Evaluates a delarr pipeline in parallel using `shard::shard_map()`. This gives proper multi-process parallelism with shared-memory I/O, including parallel reductions.

Usage

```
collect_shard(x, workers = NULL, chunk_size = NULL, optimize = TRUE)
```

Arguments

<code>x</code>	A delarr object.
<code>workers</code>	Number of worker processes. Defaults to <code>parallel::detectCores() - 1</code> .
<code>chunk_size</code>	Column chunk size for sharding. If NULL, uses the seed's <code>chunk_hint</code> or a sensible default.
<code>optimize</code>	Logical; run DAG optimizations before evaluation.

Details

Pipelines that require full-matrix evaluation (row-wise center/scale/zscore/ detrend), paired RHS delarrs (`d_map2` with two delarrs), or generic (user-supplied) reductions automatically fall back to sequential `collect()`.

Value

A materialised matrix or vector.

Examples

```
if (requireNamespace("shard", quietly = TRUE)) {
  old_conn <- getAllConnections()
  mat <- matrix(rnorm(100), 10, 10)
  darr <- delarr_shard(mat)
  result <- collect_shard(darr |> d_map(~ .x^2), workers = 2)
  all.equal(result, mat^2)
  new_conn <- setdiff(getAllConnections(), old_conn)
  for (con in new_conn) try(close(getConnection(con)), silent = TRUE)
}
```

colMeans2

Column means for delayed matrices

Description

Generic counterpart to `matrixStats::colMeans2()`. Methods are provided for `delarr` objects, but packages can extend the generic for their own delayed types.

Usage

```
colMeans2(x, ...)
```

Arguments

`x` An object for which row means should be computed.
`...` Additional arguments passed to methods.

Value

Typically a numeric vector of column means.

Examples

```
mat <- matrix(1:12, nrow = 3, ncol = 4)
darr <- delarr(mat)

# Compute column means lazily
colMeans2(darr)

# Compare with base R
colMeans(mat)
```

colMeans2.delarr	<i>Column means for a delayed matrix</i>
------------------	--

Description

Computes column means lazily via `d_reduce()`; acts as a drop-in replacement for `matrixStats::colMeans2()`.

Usage

```
## S3 method for class 'delarr'
colMeans2(x, ..., na.rm = FALSE)
```

Arguments

x	A delarr object.
...	Unused.
na.rm	Logical; remove missing values before averaging.

Value

A numeric vector of column means.

d_aperm	<i>Permute dimensions of a delayed array</i>
---------	--

Description

Permute dimensions of a delayed array

Usage

```
d_aperm(x, perm = rev(seq_along(dim(x))), chunk_size = NULL)
```

Arguments

x	A delarr.
perm	A permutation of <code>seq_along(dim(x))</code> .
chunk_size	Optional chunk size used for internal pulls.

Value

A permuted delarr.

d_center	<i>Center a delayed matrix along rows or columns</i>
----------	--

Description

Center a delayed matrix along rows or columns

Usage

```
d_center(x, dim = c("rows", "cols"), axis = NULL, na.rm = FALSE)
```

Arguments

x	A delarr.
dim	Dimension along which to subtract the mean.
axis	Integer axis for N-d arrays (alternative to dim).
na.rm	Logical; remove missing values when computing the centre.

Value

A delarr with a deferred centering operation.

Examples

```
mat <- matrix(c(1, 2, 3, 10, 20, 30), nrow = 2, ncol = 3)
darr <- delarr(mat)

# Center rows (subtract row means)
centered_rows <- darr |> d_center(dim = "rows") |> collect()
centered_rows
rowMeans(centered_rows) # Should be ~0

# Center columns (subtract column means)
centered_cols <- darr |> d_center(dim = "cols") |> collect()
colMeans(centered_cols) # Should be ~0
```

d_detrend	<i>Detrend a delayed matrix</i>
-----------	---------------------------------

Description

Removes a polynomial trend of the specified degree along the chosen dimension.

Usage

```
d_detrend(x, dim = c("rows", "cols"), axis = NULL, degree = 1L)
```

Arguments

x	A delarr.
dim	Dimension along which to fit the trend.
axis	Integer axis for N-d arrays (alternative to dim).
degree	Polynomial degree (default 1).

Value

A delarr with the detrend operation queued.

Examples

```
# Create matrix with linear trend in rows
mat <- matrix(1:12 + rep(1:4, each = 3), nrow = 3, ncol = 4)
darr <- delarr(mat)

# Remove linear trend along rows
detrended <- darr |> d_detrend(dim = "rows", degree = 1L) |> collect()
detrended

# Remove quadratic trend
quad_detrend <- darr |> d_detrend(dim = "rows", degree = 2L) |> collect()
quad_detrend
```

d_map

Apply an elementwise transformation lazily

Description

Apply an elementwise transformation lazily

Usage

```
d_map(x, f)
```

Arguments

x	A delarr.
f	A function or formula suitable for <code>rlang::as_function()</code> .

Value

A delarr representing the transformation.

Examples

```
mat <- matrix(1:12, nrow = 3, ncol = 4)
darr <- delarr(mat)

# Apply elementwise transformation with formula
squared <- darr |> d_map(~ .x^2) |> collect()
squared

# Apply with function
logged <- darr |> d_map(log1p) |> collect()
logged
```

d_map2

*Apply a binary elementwise transformation lazily***Description**

Apply a binary elementwise transformation lazily

Usage

```
d_map2(x, y, f)
```

Arguments

x	A delarr.
y	Another delarr, matrix, or numeric vector/scalar.
f	A function or formula combining two arguments.

Value

A delarr representing the fused binary operation.

Examples

```
mat1 <- matrix(1:12, nrow = 3, ncol = 4)
mat2 <- matrix(12:1, nrow = 3, ncol = 4)
darr1 <- delarr(mat1)
darr2 <- delarr(mat2)

# Binary operation between two delayed matrices
added <- d_map2(darr1, darr2, ~ .x + .y) |> collect()
added

# Binary operation with scalar
scaled <- d_map2(darr1, 10, ~ .x * .y) |> collect()
scaled
```

d_matmul	<i>Delayed matrix multiplication</i>
----------	--------------------------------------

Description

Delayed matrix multiplication

Usage

```
d_matmul(x, y, chunk_size = NULL)
```

Arguments

x	A delarr or base matrix.
y	A delarr or base matrix.
chunk_size	Optional chunk size used during block pulls.

Value

A delarr representing %*%.

d_reduce	<i>Reduce along a dimension lazily</i>
----------	--

Description

For 2D arrays use `dim = "rows"` or `"cols"`. For N-d arrays you can also supply a numeric `axis` indicating which dimension to collapse.

Usage

```
d_reduce(x, f = base::sum, dim = c("rows", "cols"), axis = NULL, na.rm = FALSE)
```

Arguments

x	A delarr.
f	A reduction function (defaults to sum).
dim	Dimension to reduce: "rows" (keep rows, collapse cols) or "cols" (keep cols, collapse rows).
axis	Integer axis to collapse (alternative to dim for N-d arrays). Takes precedence over dim when both are supplied.
na.rm	Logical; remove missing values while reducing.

Value

A delarr capturing the reduction.

Examples

```
mat <- matrix(1:12, nrow = 3, ncol = 4)
darr <- delarr(mat)

row_sums <- darr |> d_reduce(sum, dim = "rows") |> collect()
row_sums

col_means <- darr |> d_reduce(mean, dim = "cols") |> collect()
col_means
```

d_reduce_many	<i>Run multiple reductions and collect results</i>
---------------	--

Description

Run multiple reductions and collect results

Usage

```
d_reduce_many(
  x,
  fns,
  dim = c("rows", "cols"),
  na.rm = FALSE,
  chunk_size = NULL,
  simplify = TRUE
)
```

Arguments

x	A delarr.
fns	A named list of reduction functions.
dim	Reduction dimension ("rows" or "cols").
na.rm	Logical; remove missing values in each reducer.
chunk_size	Optional chunk size passed to collect().
simplify	Logical; combine equal-length outputs into a matrix.

Value

A named list (or matrix when simplify = TRUE) of reductions.

`d_scale`*Scale a delayed matrix along rows or columns*

Description

Scale a delayed matrix along rows or columns

Usage

```
d_scale(  
  x,  
  dim = c("rows", "cols"),  
  axis = NULL,  
  center = TRUE,  
  scale = TRUE,  
  na.rm = FALSE  
)
```

Arguments

<code>x</code>	A delarr.
<code>dim</code>	Dimension to scale.
<code>axis</code>	Integer axis for N-d arrays (alternative to <code>dim</code>).
<code>center</code>	Logical; subtract the mean before scaling.
<code>scale</code>	Logical; divide by the standard deviation.
<code>na.rm</code>	Logical; remove missing values when computing statistics.

Value

A delarr with a deferred scaling operation.

Examples

```
mat <- matrix(c(1, 2, 3, 10, 20, 30), nrow = 2, ncol = 3)  
darr <- delarr(mat)  
  
# Scale rows (center and divide by SD)  
scaled <- darr |> d_scale(dim = "rows") |> collect()  
scaled  
  
# Scale without centering  
scaled_only <- darr |> d_scale(dim = "rows", center = FALSE) |> collect()  
scaled_only
```

d_transpose	<i>Transpose a delayed matrix</i>
-------------	-----------------------------------

Description

Transpose a delayed matrix

Usage

```
d_transpose(x, chunk_size = NULL)
```

Arguments

x	A delarr.
chunk_size	Optional chunk size used for internal pulls.

Value

A transposed delarr.

d_where	<i>Apply a boolean mask to a delayed matrix</i>
---------	---

Description

Elements failing the predicate are replaced with fill at materialisation time.

Usage

```
d_where(x, predicate, fill = 0)
```

Arguments

x	A delarr.
predicate	A function or formula returning a logical matrix.
fill	Replacement value for elements where the predicate is FALSE.

Value

A delarr including the mask.

Examples

```

mat <- matrix(c(-1, 2, -3, 4, -5, 6), nrow = 2, ncol = 3)
darr <- delarr(mat)

# Replace negative values with 0
masked <- darr |> d_where(~ .x >= 0, fill = 0) |> collect()
masked

# Replace values below threshold with NA
filtered <- darr |> d_where(~ .x > 1, fill = NA) |> collect()
filtered

```

d_zscore	<i>Z-score a delayed matrix</i>
----------	---------------------------------

Description

Equivalent to centering and scaling with unit variance.

Usage

```
d_zscore(x, dim = c("rows", "cols"), axis = NULL, na.rm = FALSE)
```

Arguments

x	A delarr.
dim	Dimension over which to compute the z-score.
axis	Integer axis for N-d arrays (alternative to dim).
na.rm	Logical; remove missing values when computing statistics.

Value

A delarr with the z-score applied lazily.

Examples

```

mat <- matrix(c(1, 2, 3, 10, 20, 30), nrow = 2, ncol = 3)
darr <- delarr(mat)

# Z-score normalize rows
zscored <- darr |> d_zscore(dim = "rows") |> collect()
zscored

# Row means should be ~0, row SDs should be ~1
rowMeans(zscored)

```

delarr *Create a delayed matrix*

Description

Wraps an existing matrix or `delarr_seed` in the lightweight delayed pipeline. Matrix inputs are wrapped in a seed that simply slices the source object, while `delarr` inputs are returned unchanged.

Usage

```
delarr(x, ...)
```

Arguments

`x` A base matrix or a `delarr_seed` to wrap.
`...` Future extensions; currently ignored.

Value

A `delarr` object representing the delayed matrix.

Examples

```
# Create a delayed matrix from a regular matrix
mat <- matrix(1:12, nrow = 3, ncol = 4)
darr <- delarr(mat)
darr

# Operations are queued lazily
result <- darr * 2
result

# Materialize with collect()
collect(result)
```

`delarr_backend` *Wrap a custom backend as a delayed matrix*

Description

Provides a convenience helper that turns a user-supplied slice function into a ready-to-use `delarr` object.

Usage

```
delarr_backend(
  nrow,
  ncol,
  pull,
  chunk_hint = NULL,
  dimnames = NULL,
  begin = NULL,
  end = NULL
)
```

Arguments

nrow, ncol	Dimensions of the logical matrix.
pull	Function of rows and cols returning a base matrix slice.
chunk_hint	Optional preferred chunking metadata.
dimnames	Optional dimnames to expose lazily.
begin	Optional function invoked before streaming.
end	Optional function invoked after streaming.

Value

A delarr backed by the provided pull function.

Examples

```
# Create a custom backend from a pull function
data <- matrix(1:20, nrow = 4, ncol = 5)

darr <- delarr_backend(
  nrow = 4,
  ncol = 5,
  pull = function(rows = NULL, cols = NULL) {
    rows <- rows %||% seq_len(4)
    cols <- cols %||% seq_len(5)
    data[rows, cols, drop = FALSE]
  }
)
darr

# Use like any delarr
result <- darr |> d_map(~ .x * 2) |> collect()
result
```

delarr_hdf5	<i>Create a delayed array sourced from an HDF5 dataset</i>
-------------	--

Description

Uses hdf5r to lazily read slices from disk on demand.

Usage

```
delarr_hdf5(path, dataset)
```

Arguments

path	Path to the HDF5 file.
dataset	Name of the dataset within the file.

Value

A delarr that streams data from the HDF5 dataset.

Examples

```
# Create a temporary HDF5 file
tf <- tempfile(fileext = ".h5")
data <- matrix(1:20, nrow = 4, ncol = 5)

# Write test data
f <- hdf5r::H5File$new(tf, mode = "w")
f$create_dataset("X", robj = data)
f$close_all()

# Load as delayed array
darr <- delarr_hdf5(tf, "X")
darr

# Apply operations and collect
result <- darr |> d_map(~ .x * 2) |> collect()
result

# Clean up
unlink(tf)
```

delarr_mem *Create a delayed matrix from an in-memory matrix*

Description

Create a delayed matrix from an in-memory matrix

Usage

```
delarr_mem(x)
```

Arguments

x A numeric or logical matrix, or an array with at least 2 dimensions.

Value

A delarr referencing the original object.

Examples

```
# Wrap an in-memory matrix
mat <- matrix(1:12, nrow = 3, ncol = 4)
darr <- delarr_mem(mat)
darr

# Apply operations lazily
result <- darr |> d_center(dim = "rows") |> collect()
result
```

delarr_mmap *Create a delayed matrix from a memory-mapped file*

Description

Uses the mmap package to lazily read slices from a binary file on demand. The file must contain raw numeric data in column-major order (R's default).

Usage

```
delarr_mmap(path, nrow, ncol, mode = NULL)
```

Arguments

path Path to the binary file containing matrix data.
nrow Number of rows in the matrix.
ncol Number of columns in the matrix.
mode mmap mode object specifying data type. Default is double().

Value

A delarr that streams data from the memory-mapped file.

Note

This backend supports 2D matrices only. For N-d arrays, use `delarr_hdf5()` or wrap an in-memory array with `delarr()`.

Examples

```
# Create a binary file with matrix data
mat <- matrix(1:20, nrow = 4, ncol = 5)
tf <- tempfile()
writeBin(as.double(mat), tf)

# Load as delayed array
darr <- delarr_mmap(tf, nrow = 4, ncol = 5)
darr

# Apply operations and collect
result <- darr |> d_map(~ .x * 2) |> collect()
result

# Clean up
unlink(tf)
```

delarr_seed

Construct a seed backend for delarr

Description

Seeds encapsulate storage access for delayed matrices. They define matrix dimensions and a `pull()` function that returns materialised slices.

Usage

```
delarr_seed(
  nrow,
  ncol,
  pull,
  chunk_hint = NULL,
  dimnames = NULL,
  begin = NULL,
  end = NULL
)
```

Arguments

nrow, ncol	Number of rows and columns.
pull	A function accepting rows and cols indices and returning a base matrix slice.
chunk_hint	Optional list describing preferred chunk sizes (e.g. <code>list(cols = 4096L)</code>).
dimnames	Optional list of dimnames to expose lazily.
begin	Optional function invoked before streaming begins.
end	Optional function invoked after streaming completes.

Value

An object of class `delarr_seed`.

Examples

```
# Create a custom seed with a pull function
data <- matrix(1:12, nrow = 3, ncol = 4)

seed <- delarr_seed(
  nrow = 3,
  ncol = 4,
  pull = function(rows = NULL, cols = NULL) {
    rows <- rows %||% seq_len(3)
    cols <- cols %||% seq_len(4)
    data[rows, cols, drop = FALSE]
  }
)
seed

# Wrap in delarr() to use with lazy operations
darr <- delarr(seed)
result <- darr |> d_map(~ .x * 2) |> collect()
result
```

`delarr_seed_nd`
Construct an N-dimensional seed backend for delarr

Description

Creates a seed for arrays with 2 or more dimensions. The pull function receives a list of per-dimension index vectors and returns the corresponding sub-array.

Usage

```
delarr_seed_nd(
  dims,
  pull,
  chunk_hint = NULL,
```

```

    dimnames = NULL,
    begin = NULL,
    end = NULL
  )

```

Arguments

<code>dims</code>	Integer vector of dimension extents (length ≥ 2).
<code>pull</code>	A function accepting a single argument <code>indices</code> — a named or positional list of integer vectors (one per dimension, or <code>NULL</code> for "all") — and returning an array with the requested sub-dimensions.
<code>chunk_hint</code>	Optional list describing preferred chunk sizes.
<code>dimnames</code>	Optional list of <code>dimnames</code> (one element per dimension).
<code>begin</code>	Optional function invoked before streaming begins.
<code>end</code>	Optional function invoked after streaming completes.

Value

An object of class `delarr_seed`.

Examples

```

arr <- array(seq_len(24), dim = c(3, 4, 2))
seed <- delarr_seed_nd(
  dims = c(3, 4, 2),
  pull = function(indices) {
    idx <- lapply(seq_along(dim(arr)), function(k) indices[[k]] %||% seq_len(dim(arr)[k]))
    do.call("[", c(list(arr), idx, list(drop = FALSE)))
  }
)
dim(seed)

```

`delarr_shard`

Create a delayed array backed by shared memory

Description

Wraps a numeric matrix or array into `shard`'s shared memory, returning a `delarr`. The shared ALTREP vector is stored on the seed so that `collect_shard()` can reuse it without re-sharing (zero-copy).

Usage

```
delarr_shard(x, backing = "auto")
```

Arguments

x A numeric matrix or array.
backing Backing type passed to shard::share().

Value

A delarr backed by shared memory.

Examples

```
if (requireNamespace("shard", quietly = TRUE)) {  
  mat <- matrix(rnorm(20), 4, 5)  
  darr <- delarr_shard(mat)  
  collect(darr)  
}
```

dim.delarr

Dimensions of a delayed array

Description

Computes the realised dimensions after taking queued slice and reduce operations into account.

Usage

```
## S3 method for class 'delarr'  
dim(x)
```

Arguments

x A delarr.

Value

An integer vector of dimension extents.

dim.delarr_seed	<i>Dimensions for a delarr_seed</i>
-----------------	-------------------------------------

Description

Dimensions for a delarr_seed

Usage

```
## S3 method for class 'delarr_seed'  
dim(x)
```

Arguments

x A delarr_seed.

Value

An integer vector of dimension extents.

dimnames.delarr	<i>Dimension names for a delayed array</i>
-----------------	--

Description

Dimension names for a delayed array

Usage

```
## S3 method for class 'delarr'  
dimnames(x)
```

Arguments

x A delarr.

Value

A list of per-dimension names or NULL placeholders.

explain	<i>Explain a delayed execution plan</i>
---------	---

Description

Explain a delayed execution plan

Usage

```
explain(
  x,
  chunk_size = NULL,
  chunk_margin = c("cols", "rows"),
  target_bytes = NULL,
  optimize = TRUE
)
```

Arguments

x	A delarr.
chunk_size	Optional chunk size hint.
chunk_margin	Chunking axis for non-reduction materialization.
target_bytes	Optional memory budget used for adaptive chunking.
optimize	Logical; whether to explain the optimized DAG.

Value

An object of class `delarr_explain`.

hdf5_writer	<i>HDF5 writer for streaming collect()</i>
-------------	--

Description

Creates or extends an HDF5 dataset so that `collect(x, into = writer)` can stream column blocks directly to disk without materialising the full matrix in memory.

Usage

```
hdf5_writer(path, dataset, ncol, chunk = c(128L, 4096L), compression = 4L)
```

Arguments

path	Path to the HDF5 file. The file is created if it does not exist.
dataset	Name of the dataset to create or update.
ncol	Total number of columns that will be written. The writer uses this to size the target dataset up-front.
chunk	Integer vector of length two giving the chunk size (rows, cols) for the target dataset (optional).
compression	Gzip compression level (0-9). Use 0 for no compression, higher values for better compression at cost of speed. Default is 4. Use NULL to disable compression entirely.

Value

A writer object with `$write()` and `$finalize()` methods understood by `collect()`.

Examples

```
# Create source data in a temp HDF5 file
tf_in <- tempfile(fileext = ".h5")
data <- matrix(1:20, nrow = 4, ncol = 5)
f <- hdf5r::H5File$new(tf_in, mode = "w")
f$create_dataset("X", robj = data)
f$close_all()

# Load, transform, and stream to output file
darr <- delarr_hdf5(tf_in, "X")
transformed <- darr |> d_center(dim = "cols")

tf_out <- tempfile(fileext = ".h5")
writer <- hdf5_writer(tf_out, "result", ncol = ncol(transformed), compression = 4L)
collect(transformed, into = writer)

# Verify output
g <- hdf5r::H5File$new(tf_out, mode = "r")
result <- g[["result"]]$read()
g$close_all()
result

# Clean up
unlink(c(tf_in, tf_out))
```

Description

Supports elementwise operations between delayed matrices or between a delayed matrix and scalars/matrices.

Usage

```
## S3 method for class 'delarr'
Ops(e1, e2)
```

Arguments

e1, e2 Operands supplied by the R math group generics.

Value

A delarr representing the fused operation.

optimize_delarr	<i>Optimize a delayed pipeline</i>
-----------------	------------------------------------

Description

Applies lightweight algebraic simplifications to reduce unnecessary work during collect().

Usage

```
optimize_delarr(x)
```

Arguments

x A delarr object.

Value

A delarr with an optimized operation list.

print.delarr	<i>Pretty-print a delayed matrix</i>
--------------	--------------------------------------

Description

Pretty-print a delayed matrix

Usage

```
## S3 method for class 'delarr'
print(x, ...)
```

Arguments

x A delarr.
 ... Unused.

Value

The original object, invisibly.

profile_collect	<i>Profile collect() runtime</i>
-----------------	----------------------------------

Description

Profile collect() runtime

Usage

```
profile_collect(x, reps = 3L, ...)
```

Arguments

x	A delarr.
reps	Number of repetitions.
...	Additional arguments forwarded to collect().

Value

An object of class delarr_profile.

read_hdf5	<i>Read a matrix from an HDF5 file</i>
-----------	--

Description

Simple convenience function to read a matrix from an HDF5 dataset. For lazy/streaming access, use delarr_hdf5() instead.

Usage

```
read_hdf5(path, dataset)
```

Arguments

path	Path to the HDF5 file.
dataset	Name of the dataset to read.

Value

The matrix stored in the dataset.

Examples

```
# Write and read back
mat <- matrix(1:20, nrow = 4, ncol = 5)
tf <- tempfile(fileext = ".h5")
write_hdf5(mat, tf, "X")
read_hdf5(tf, "X")

# Clean up
unlink(tf)
```

rowMeans2

Row means for delayed matrices

Description

Generic counterpart to `matrixStats::rowMeans2()`. Methods are provided for `delarr` objects, but packages can extend the generic for their own delayed types.

Usage

```
rowMeans2(x, ...)
```

Arguments

`x` An object for which row means should be computed.
`...` Additional arguments passed to methods.

Value

Typically a numeric vector of row means.

Examples

```
mat <- matrix(1:12, nrow = 3, ncol = 4)
darr <- delarr(mat)

# Compute row means lazily
rowMeans2(darr)

# Compare with base R
rowMeans(mat)
```

rowMeans2.delarr	<i>Row means for a delayed matrix</i>
------------------	---------------------------------------

Description

Computes row means lazily via `d_reduce()`; acts as a drop-in replacement for `matrixStats::rowMeans2()`.

Usage

```
## S3 method for class 'delarr'
rowMeans2(x, ..., na.rm = FALSE)
```

Arguments

<code>x</code>	A delarr object.
<code>...</code>	Unused.
<code>na.rm</code>	Logical; remove missing values before averaging.

Value

A numeric vector of row means.

shard_writer	<i>Shared-memory writer for streaming collect()</i>
--------------	---

Description

Creates a writer object backed by `shard::buffer()` conforming to delarr's writer protocol. Pass to `collect(x, into = shard_writer(...))` to stream results into shared memory.

Usage

```
shard_writer(nrow, ncol, backing = "auto")
```

Arguments

<code>nrow, ncol</code>	Dimensions of the output matrix.
<code>backing</code>	Backing type passed to <code>shard::buffer()</code> .

Value

A writer list with `$write()`, `$finalize()`, `$result()`, and `$close()` methods.

Note

This writer supports 2D matrices only. N-d array collection does not currently support writer-style into targets.

Examples

```
if (requireNamespace("shard", quietly = TRUE)) {
  mat <- matrix(rnorm(20), 4, 5)
  darr <- delarr(mat)
  w <- shard_writer(4, 5)
  collect(darr |> d_map(~ .x * 2), into = w)
  w$result()
  w$close()
}
```

write_hdf5

Write a matrix to an HDF5 file

Description

Simple convenience function to write a matrix to an HDF5 dataset. For streaming writes during `collect()`, use `hdf5_writer()` instead.

Usage

```
write_hdf5(x, path, dataset, compression = 4L)
```

Arguments

<code>x</code>	A matrix to write.
<code>path</code>	Path to the HDF5 file. Created if it doesn't exist.
<code>dataset</code>	Name of the dataset to create.
<code>compression</code>	Gzip compression level (0-9), or NULL for no compression.

Value

The path to the HDF5 file (invisibly).

Examples

```
# Write a matrix to HDF5
mat <- matrix(1:20, nrow = 4, ncol = 5)
tf <- tempfile(fileext = ".h5")
write_hdf5(mat, tf, "X")

# Read it back as a delarr
darr <- delarr_hdf5(tf, "X")
collect(darr)
```

```
# Clean up  
unlink(tf)
```

Index

[.delarr, 3

as.matrix.delarr, 3

block_apply, 4

collect, 5

collect_shard, 6

colMeans2, 7

colMeans2.delarr, 8

d_aperm, 8

d_center, 9

d_detrnd, 9

d_map, 10

d_map2, 11

d_matmul, 12

d_reduce, 12

d_reduce_many, 13

d_scale, 14

d_transpose, 15

d_where, 15

d_zscore, 16

delarr, 17

delarr(), 21

delarr_backend, 17

delarr_hdf5, 19

delarr_hdf5(), 21

delarr_mem, 20

delarr_mmap, 20

delarr_seed, 21

delarr_seed_nd, 22

delarr_shard, 23

dim.delarr, 24

dim.delarr_seed, 25

dimnames.delarr, 25

explain, 26

hdf5_writer, 26

Ops.delarr, 27

optimize_delarr, 28

print.delarr, 28

profile_collect, 29

read_hdf5, 29

rowMeans2, 30

rowMeans2.delarr, 31

shard_writer, 31

write_hdf5, 32